



## HANDHELD TERMINALS



Specialists in portable data collection systems







### An efficient and highly versatile data capture solution for all stages of the supply chain.

A modern 'smartphone' style device, the ACD M2Smart®SE revolutionises mobile data capture. Robust ABS housing with large 4.8" capacitive touchscreen, the M2Smart®SE is designed with a unique ACD patented 'slide mechanism' facilitating functionality modules to be attached quickly and without tools; whilst ACD's own Android™ Industrial+ operating system ensures flawless reliability.

A wide range of 'plug 'n play' modules include keyboard, pistol grip, 1D/2D long-range barcode scanner, RFID reader, label printers & temperature sensor. The individual modules can be exchanged on the upper or lower slide mechanisms at any time without interrupting workflow.

Android™ Industrial+ ACD Group's own operating system can be adapted to specific customer requirements. ACD provides post-sales support, incorporates security updates, troubleshooting and rapid response to security gaps. Data security is guaranteed - no data is transferred to third parties.



#### M2SMART®SE HANDHELD TERMINAL



## 0,000

Keyboard

#### **TECHNICAL SPECIFICATIONS**

Case: ABS/PC

Protection: IP41/IP54/IP65 \*
Operating temperature: -20 °C to 50 °C \*\*

**Storage temperature:** -20 °C to 60 °C (with battery removed)

**Dimensions:** 170 x 82 x 28 mm (L x W x H)

Weight: Approx. 390g

Power supply: 3.8V Quick-change rechargeable battery, li-ion with 22.8 Wh

(6,000 mAh), docking station incl. charger for spare battery

**Display:** 4.8" colour TFT Display with LED backlight, 1280 x 720 pixels,

280 cd/m2, 3 Status LED

**Touchscreen:** Capacitive, surface hardness according to MOHS category 5-6

**Keyboard:** Side On / Off key

**Barcode scanner:** 2D scanner (SE4710) integrated in housing (side scanner keys)

Camera: 5 MP auto-focus camera with lighting

Processor: NXP® i.MX 8M Mini, 4x Cortex A53 (4x 1.8 GHz) &

Cortex M4 (1x 400 MHz)

Memory: ACD Standard: 16 GB Flash, 2 GB RAM.

Optional: 32 GB RAM Flash, 4 GB Flash

Operating system: Android<sup>TM\*\*\*</sup> Industrial+



Protective Caps

Temperature Sensor





M2Smart®SE in Cradle

#### **OPTIONS**

- WLAN according to IEEE 802.11a/b/g/n/ac/d/h/e/i/r/w/v incl. BT-compatible close-range network 5.0
- WLAN Security¹: WEP, WPA, IEEE802.11i (Personal and Enterprise), WPA2, WPA2-PSK, 802.1x: authentication
- M2 Temperature:

Attachable temperature sensor to measure core & surface temperature

M2Key16

Attachable silicone keyboard with 16 keys

■ M2UHF-RFID

Attachable UHF-RFID reader for reading UHF-RFID tags

SOTI ® MobiControl

#### **ACCESSORIES**

- Docking Station: DS2Smart®
- M2Logisitcs Protection caps
- M2Grip5

<sup>\*</sup> Conditions apply


<sup>\*\*</sup> The device should only be used in deep-freeze area after start-up process

 $<sup>^{\</sup>star\star\star}$  Registered trademark - Android  $^{\mathsf{TM}}.$  Android is a trademark of Google LL

<sup>&</sup>lt;sup>1</sup> Standard codification validated by ACD



## HasciSE WRIST-MOUNT BARCODE SCANNER



#### 'Hands-free' scanning with HasciSE: Wrist Mount / Wearable barcode scanner.

Robust, compact and lightweight, the ACD HasciSE can be used in all stages of logistics, retail and other commercial or industrial processes.

Similar to a 'matchbox' in size and weighing only 45grams, HasciSE is one of the smallest & lightest wearable barcode scanners on the current market. With a minimum battery runtime of one typical shift operators can work 'hands free' increasing productivity and accuracy.

Designed to be 'plug & play' solution, HasciSE can be quickly & easily paired with any device that supports BT4.0 and later with the 'ACD EasyToConnect app' providing a secure connection eliminating possible interference from other nearby devices.

The 1D & 2D imager (SE4770) can be manually triggered with the device button or finger switch built into the ACD hand strap or full hands-free via proximity sensor, ensuring fast efficient scanning performance in all environments.

For versatility HasciSE can be supplied with a mounting plate and extractable zipper-strip that can be attached to a belt or utility vest.

- Compatible with any B-T device 4.0 and above
- Quick, Easy & Secure device pairing with ACD 'EasyToConnect' app
- Audible, Visual & Vibration scan feedback
- Long battery run time
- IP54
- 3-year warranty



## **HasciSE**WRIST-MOUNT BARCODE SCANNER



#### **TECHNICAL SPECIFICATIONS**

Case: ABS
Protection: IP54

Operating temperature: -20 °C to 50 °C to 50 °C to 40 °C storage temperature: -20 °C to 20 °C to 20 °C

**Dimensions:** 56 x 45 x 14 mm (L x W x H)

Weight: 45 g

Power supply: Battery, li-po with 1.66 Wh (450 mAh/3.7 V), Docking station

Display: Status LED

**Keyboard:** On/Off Button & Scanner Button

Barcode scanner: 1D & 2D imager (SE4770) integrated in housing.

Optional: DotCode Scanner

Interfaces: BT-compatible close-range network 4.0

Compatibility with all BT-enabled Android™ devices: BT 4.0 and above (Windows version also available)



#### **SPECIAL FEATURES**

- Scan trigger: scanner key, finger switch (on hand strap) or proximity sensor
- Audible, Visual & Vibration scan feedback
- Pairing via BT-compatible close-range network
- Easy & secure pairing with ACD 'EasyToConnect' App



- Docking station: DSHasciSE
- ACD Wrist Strap incl. Finger Switch
- HasciSE Zipper-Strip (Square Connector)
- HasciSE Zipper-Strip (Round Connector)
- HasciSE mounting plate



2 HasciSE units in charging cradle



HasciSE three quarter view



HasciSE charging connectors







The new generation of ACD handheld - a perfect combination of 'smartphone' screen and rugged industrial device, the M270 is a powerful data capture terminal for intensive mobile scanning applications in the most demanding industrial environments.

The tough ABS plastic case with built in protection buffering offers durability against drops, windblown rain and dust, whilst the powerful NXP\*\* processor, long battery life and ACD's own Android™ Industrial+ operating system ensures flawless reliability.

The M270 is equipped with a 1D scanner (SE965), 3.5" colour touch sensitive TFT display with LED backlight, quick entry keyboard, two side scanner keys and ten user-programable function keys. Units are BT-compatible (close-range network)

Wi-Fi connectivity is standard with the M270. Host connectivity is provided via the DS270 docking station. A comprehensive range of accessories: pistol grip, additional batteries, single/multi-battery chargers, vehicle mount kits and bags/belt holsters are available.

**Android™ Industrial+** ACD Group's own operating system can be adapted to specific customer requirements. ACD provides post-sales support, incorporates security updates, troubleshooting and rapid response to security gaps. Data security is guaranteed - no data is transferred or can be shared with third parties.



#### M270 HANDHELD TERMINAL





M270 with Pistol Grip



M270 in Cradle & Spare Battery



M270 RAM Mount





M270 Scanner

#### **TECHNICAL SPECIFICATIONS**

Case: ABS
Protection: IP54

Operating temperature: O °C to 40 °C

Storage temperature:  $-20 \, ^{\circ}\text{C}$  to 70  $^{\circ}\text{C}$  (with battery removed)

Dimensions:  $219 \times 62/83 \times 39/41 \, \text{mm} \, (\text{L x W x H})$ 

Weight: Approx. 500g

**Power supply:** Quick-change battery: li-ion with 24.5 Wh (3,400 mAh/7.2 V),

docking station or battery charger

**Display:** 3.5" colour TFT Display with LED backlight, 480 x 640 pixels,

400 cd/m<sup>2</sup>, Status LED

**Touchscreen:** Capacitive, minimum surface hardness 6H

**Keyboard:** Quick-entry keyboard with alphanumeric function, 15 mm space

between keys, 15 keys in hard case design, 10 function keys

Barcode scanner: 1D scanner (SE965) integrated in housing with side scanner keys

Processor: NXP® \* i.MX6 Dual Lite, 1 GHz (DualCore, Cortex A9)

**Memory:** 8 GB Flash, 1 GB RAM, larger memory optionally available

**Operating system:** Android™\*\* Industrial+

Interfaces: USB OTG

#### **OPTIONS**

- 2D Scanner (SE4500)
- 2D Long-range scanner (EX25) with pistol grip
- WLAN according to IEEE 802.11 a/b/g/n, WLAN Security¹: WEP, WPA, IEEE802.11i (WPA2), WPA2-PSK, Personal and Enterprise 802.11x: PEAP-MSCHAPv2, EAP-TLS
- BT-compatible close-range network
- Various software products including 'EasyToConfig', etc.

#### **ACCESSORIES**

- Docking station: DS260
- Pistol grip
- Zipper strip
- Battery charger: 1-way & 5-way
- Vehicle mount device (on request)
- Various holsters/bags

<sup>\*</sup> Registered trademark - NXP 'Standard codification validated by ACD

\*\* Registered trademark - Android™ Subject to technical modifications

Android is a trademark of Google LL



The ACD M260TE is a powerful data capture terminal for intensive mobile scanning applications with 'Microsoft Windows EC7' operating system.

Tough ABS plastic case with built in protection buffering offers durability against drops, windblown rain and dust, whilst the powerful NXP\*\* processor and long battery life ensures flawless reliability.

The M260TE is equipped with a large touch sensitive high contrast TFT display with LED backlight, a choice of two keyboards, two side scanner keys and ten user programmable function keys. Units are BT-compatible (close-range network) with the choice of scanner options: 1D midrange, 1D long-range or 2D short or 2D long-range.

Wi-Fi connectivity is standard with all versions of the M260TE.

Host connectivity is provided via the DS260 docking station. A comprehensive range of accessories: pistol grip, additional batteries, single/multi-battery chargers, vehicle mount kits and bags/belt holsters are available.

5MP auto focus camera w/light. GPS & UMTS available on request.



### **M260TE**HANDHELD TERMINAL

## 



Silicone keyboard with backlit keys



Docking station



Pistol grip



Battery charger - 5 fold/1-fold



Mounting device for vehicles



RAM mounting device



Zipper and Strip



Various bags/belt holster

#### **TECHNICAL SPECIFICATIONS**

Case: ABS
Protection: IP54

Operating temperature: O °C to 40 °C

Storage temperature: -20 °C to 70 °C (with battery removed)

Dimensions: 219 x 62/83 x 39/41 mm (L x W x H)

Weight: Approx. 500 g

Power supply: Li-lon with 24.5 Wh (3.400 mAh/7.2V) quick-change battery,

docking station or battery charger

**Display:** 3.5" colour TFT Display with LED backlight, 240 x 320 pixels,

640 cd/m<sup>2</sup>, Status LED

**Touchscreen:** Resistive, minimum surface hardness 3H

**Keyboard:** Quick-entry keyboard with alphanumeric function, 15 mm space

between keys, 15 keys in hard case design, 10 function keys

Barcode scanner:

1D scanner integrated in housing (side scanner keys)

Processor:

NXP\* ® i.MX6 Dual Lite, 1 GHz (DualCore, Cortex A9)

Memory:

4 GB Flash, 1 GB RAM, larger memory optionally available

Operating system: Windows®\*\* Embedded Compact 7 (EC7)

Interfaces: USB OTG, microSD card

#### **OPTIONS**

- 1D Long-range scanner with grip
- 2D scanner
- 2D Long-range scanner with grip
- WLAN according to IEEE 802.11 a/b/g/n incl. BT-compatible close-range network; CCXv4 WLAN Security¹: WEP, WPA, IEEE802.11 i (WPA2), WPA2-PSK, Personal and Enterprise, 802.1 x: PEAP-MSCHAPv2, PEAP TLS, PEAP-GTC, EAP-FAST, EAP-TLS, EAP-TTLS, LEAP
- Illuminated silicone keyboard
- Mobile wireless multi-band (LTE, UMTS/HSPA+, GSM/GPRS/EDGE)
- Ivanti® Products, SOTI® MobiControl

#### **ACCESSORIES**

- Docking station DS260 Pistol grip
- Battery charger 1-way & 5-way
- Mounting devices
- Zipper Strip
- Various holsters & bags

<sup>\*</sup> Registered trademark - NXP



## PHARMACEUTICAL & FOOD ANDROID<sup>TM</sup> o/s



Specifically developed for hygiene critical working environments, the M266SE is a robust and versatile solution for the pharmaceutical or food manufacturing industry.

IP65 rated, the tough ABS housing offers increased durability against dust and low-pressure water jets. Units are designed without edges to prevent dirt build up and equipped with a washable membrane keyboard compatible with industry standard cleaning agents.

The M266SE Pharmaceutical features an antimicrobial coating for use in sterile environments Both versions of the M266SE can be configured with either a 1D or 2D laser scanner and are equipped with a large touch sensitive − high contrast TFT display with LED backlight and six user-programable function keys, whilst the Android<sup>™</sup> Industrial + operating system and powerful NXP processor ensures flawless reliability.

Wi-Fi connectivity is standard with all versions whilst host connectivity is provided via the DS266 docking station.

Android™ Industrial+ ACD Group's own operating system can be adapted to specific customer requirements. ACD provides post-sales support, incorporates security updates, troubleshooting and rapid response to security gaps. Data security is guaranteed - no data is transferred or can be shared with third parties.



## PHARMACEUTICAL & FOOD HANDHELD TERMINALS

# MACO MACO

M266 Pharmaceutical in Docking Station





#### **TECHNICAL SPECIFICATIONS**

Case: ABS
Protection: IP65

Operating temperature: -20 °C to 45 °C

Storage temperature: -20 °C to 70 °C (with battery removed) Dimensions:  $224 \times 92 \times 36/157$ mm mm (L x W x H)

Weight: Approx. 600g

**Power supply:** li-ion with 24.5 Wh (3,400 mAh/7.2 V) docking station

**Display:** 3,5" colour TFT Display with LED backlight, 240 x 320 pixels,

640 cd/m<sup>2</sup>, Status LED

Touchscreen: Resistive, minimum surface hardness 3H

M266SE Pharmaceutical Washable membrane keyboard with antimicrobial coating

**Keyboard only:** 21 keys incl. 6 function keys

M266SE FoodWashable membrane keyboardKeyboard only:21 keys incl. 6 function keys

Barcode scanner:

1 D scanner integrated in housing (scanner key on grip)

Processor:

NXP®\* i.MX6 Dual Lite, 1 GHz (DualCore, Cortex A9)

Memory:

8 GB Flash, 1 GB RAM, larger memory option available

Operating system: Android™\*\* Industrial+

Interfaces: WLAN according IEEE 802.11 a/b/g/n incl. BT-compatible

close-range network WLAN Security1: WEP, WPA,

IEEE802.11i (WPA2), WPA2-PSK, Personal and Enterprise 802.11x: PEAP-MSCHAPv2, EAP-TLS, microUSB (intern)

#### **OPTIONS**

2D scanner

#### **ACCESSORIES**

- Docking station
- M622xx Mounting Bracket

\* Registered trademark - NXP

\*\* Registered trademark - Android™

Android is a trademark of Google LL

<sup>1</sup>Standard codification validated by ACD Subject to technical modifications





Specialists in portable data collection systems



